

14 - Flamedxx

- Flamedxx Fire Retardant OSB
- Class A rating on both 10 and 30 minute ASTM E-84 tests
- 7/16, 19/32 23/32SE and 23/32T&G
- IAPMO ES 0158 code evaluation report
- Meets Canadian Test CAN/ULC S102
- Flame Spread Index – 10
- Complies with 2006 IBC and 2006 IRC
- QAI Listing B1032
- Find test results at our website www.arndtandherman.com
- PS 2-04 structural rating
- Orange tint to identify product
- All the advantages of OSB over plywood
- Used in homes, schools, hospitals, apartments and condos
- NY City Bldg. Dept. MEA# 628-06-M
- Approve by Calgary Fire Marshall for "Protection of Adjacent Building"
- Smoke Developed Index – 30
- Use for roof sheathing, wall sheathing, subfloors and single layer floors

Fire Retardant OSB

SE	TX	Description	Item No.	Pieces Per Unit	Pieces Per Truck	Factory Direct Pricing	Warehouse Pricing
SE	TX	Flamedxx 4'x 8'- 7/16"	FD04080716	78	936	Call Office	Call Office
SE	TX	Flamedxx 4'x 8'- 19/32"	FD04081932	60	720	Call Office	Call Office
SE	TX	Flamedxx 4'x 8'- 23/32" TG	FD04082332TG	50	600	Call Office	Call Office
SE	TX	Flamedxx 4'x 8'- 23/32"	FD04082332	50	600	Call Office	Call Office